


## 10/8 BANCOWINE



## EXPOWINE 6

Espositore per bar e ristoranti facile da posizionare e utilizzare  
 Display case for bars and restaurants, easy to position and use  
 Présentoir pour bar et restaurant facile à mettre en place et à utiliser  
 Ausstellungsitrine für Bar und Restaurant von einfacher Aufstellung und Gebrauch  
 Expositor para bares y restaurantes fácil de colocar y utilizar

Struttura in PVC colore legno scuro  
 PVC structure, dark wood colour  
 Structure en PVC couleur bois foncé  
 Struktur aus dunklem holzfarbigem PVC  
 Estructura de PVC color madera oscura


Centralina elettronica  
 Electronic cabinet  
 Central électronique  
 Elektronisches Steuergehäuse  
 Centralita electrónica

Area espositiva  
 Exhibition area  
 Zone d'exposition  
 Ausstellungsfläche  
 Area expositiva  
 0,29 m<sup>2</sup>



0,75 lt. bottles N° 6



## WINECONSOLLE 6



## WINECONSOLLE 8












Diametro bottiglie max. 80 mm.  
 Bottles max diameter. 80 mm.  
 Diamètre bouteilles maximum 80 mm.  
 Flaschendurchmesser maximal. 80 mm.  
 Diámetro botellas max. 80 mm.

Selezione della temperatura per vino rosso o bianco / Temperature selection for red and white wines / Sélection de la température pour vin rouge ou blanc / Temperaturwahl für Rot- oder Weisswein / Selección de la temperatura del vino tinto o blanco


Esterno acciaio inox, interno in alluminio / Inside stainless steel outside aluminium / Extérieur en acier inox, intérieur en aluminium / Ausseres aus rostfreiem Stahl, Inneres aus Aluminium / Exterior en acero inoxidable, interior en aluminio



Modello Model Modèle Modell Modelo	Potenza Power Puissance Gesamtleistung Potencia	Tensione Tension Tension Spannung Tension	Temperatura Temperature Temperature Temperatur Temperatura	Refrigerazione Refrigeration Refrigeration Kuehlung Refrigeracion	Sbrinamento Defrosting Degivrage Enteisung Desescarche	Gas refrigerante Cooling gas Gaz réfrigérant Kühlgas Gas refrigerante	Bottiglie bottles Bouteilles Flaschen Botellas	Peso netto Net weight Poids net Nettogewicht Peso neto
 <b>EXPOWINE 6</b>	Watt 190	230v/1/50Hz	°C +8/+15			R 134a	N° 6	Kg 20
 <b>WINECONSOLLE 6</b>	Watt 94	230v/1/50Hz	°C +5/+18			R 134a	N° 6	Kg 16
 <b>WINECONSOLLE 8</b>	Watt 94	230v/1/50Hz	°C +5/+18			R 134a	N° 8	Kg 17




**LAMPO 3 (Schockfroster)**



**Struttura in lamiera verniciata**  
Varnished sheet structure  
Structure en tôle vernie  
Struktur aus lackiertem Blech  
Estructura de chapa pintada

**Refrigerazione con liquido antigelo**  
/ Refrigeration with anti-freezing liquid  
Refrigeration avec liquide antigel /  
Kühlung mit flüssigen Frostschutzmittel  
/ Refrigeración con liquido anticongelante

**Centralina elettronica**  
Electronic cabinet  
Central électronique  
Elektronisches Steuergehäuse  
Centralita electrónica




**LAMPO 2 (Schockfroster)**  
**LAMPO 3 (Schockfroster)**

Aspettare che sia acceso da 6-7 ore prima di usarlo, in modo da raggiungere una temperatura di -30°/-35°C. La bottiglia sarà raffreddata ad una velocità di -2°C al minuto.

Before use please wait 6-7 hours functioning, to reach the temperature of -30/-35°C. Bottle will be cooled with speed of -2°C per minute. / Attendre 6-7 heures avant de l'utiliser pour arriver ur temperature de -30/-35°C. La Bouteille sera réfrigérée à une vitesse de -2°C par minute. / das Gerät muss ca 6-7 Stunden angeschaltet sein vor d Benutzung, damit es die Temperatur von -30°/-35°C erreichen kann. Die Flasche kühlt bei einer Geschwindigkeit von -2°C pro Minute. / Esperar 6-7 horas antes de utilizarlo, para alcanzar temperatura de -30/-35°C. La botella será enfriada a ur velocidad de -2°C por minutos.

**LAMPO 2 (Schockfroster)**




Modello Model Modèle Modell Modelo	Potenza Power Puissance Gesamtleistung Potencia	Tensione Tension Tension Spannung Tension	Temperatura Temperature Temperature Temperatur Temperatura	Refrigerazione Refrigeration Refrigeration Kühlung Refrigeracion	Sbrinamento Defrosting Degivrage Enteisung Desescarche	Gas refrigerante Cooling gas Gaz réfrigérant Kühlgas Gas refrigerante	Bottiglie bottles Bouteilles Flaschen Botellas	Peso netto Net weight Poids net Nettogewicht Peso neto
<b>LAMPO 2 (Schockfroster)</b>	Watt 265	230v/1/50Hz	°C -35			R 134a	N° 2	Kg 32
<b>LAMPO 3 (Schockfroster)</b>	Watt 300	230v/1/50Hz	°C -35			R 134a	N° 3	Kg 34



Dati di collaudo - Test details - Détails d'essai - Prüfungsergebnisse - Datos de ensayo - MAX = (25°C - % U.R. 60)

EUROLINE  
BIRRA  
MERCATI SPECIALI  
LABORATORI PASTICCERIA  
RISTORAZIONE  
PIZZERIA  
ESPOSIZIONE  
SUPERMERCATI  
HYPERMARKET  
ATTREZZATURE COMPLEMENTARI

## 10/9 EXPO BAR



## VODKA 6




Struttura in lamiera verniciata.  
Cupola in plexiglas.  
Varnished sheet structure. Plexiglass dome.  
Structure en tôle vernie. Calotte en plexiglas.  
Struktur aus lackiertem Blech. Haube aus Plexiglas.  
Estructura de chapa pintada. Cúpula de plexiglas.

Termostato meccanico  
Mechanical thermostat  
Thermostat mécanique  
Mechanischer Temperaturregler  
Termóstato mecánico

Capacità: 6 bottiglie più bicchieri.  
Capacity: 6 bottles + glasses  
Capacité: 6 bouteilles + verres  
Kapazität: 6 Flaschen + Gläser  
Capacidad: 6 botellas + vasos

## FRESH YOGURT









Vetrinetta per latticini  
Dairy products showcase  
Vitrine Réfrigérée pour produits laitiers  
Kühltheke fuer Milchprodukte  
Vitrina para lacteos

Struttura in lamiera verniciata.  
Cupola in plexiglas.  
Varnished sheet structure. Plexiglass dome.  
Structure en tôle vernie. Calotte en plexiglas.  
Struktur aus lackiertem Blech. Haube aus Plexiglas.  
Estructura de chapa pintada. Cúpula de plexiglas.

Termostato meccanico  
Mechanical thermostat  
Thermostat mécanique  
Mechanischer Temperaturregler  
Termóstato mecánico



Modello Model Modèle Modell Modelo	Potenza Power Puissance Gesamtleistung Potencia	Tensione Tension Tension Spannung Tension	Temperatura Temperature Temperature Temperatur Temperatura	Refrigerazione Refrigeration Refrigeration Kuehlung Refrigeracion	Sbrinamento Defrosting Degivrage Enteisung Desescarche	Gas refrigerante Cooling gas Gaz réfrigérant Kühlgas Gas refrigerante	Peso netto Net weight Poids net Nettogewicht Peso neto
 <b>VODKA 6</b>	Watt 135	230v/1/50Hz	°C 0/-13			R 134a	Kg 18
 <b>FRESH YOGURT</b>	Watt 225	230v/1/50Hz	°C 0/+5			R 134a	Kg 23,5