

TPWE "EXECUTIVE" SERIES PALLET TRUCK SCALE



Pallet truck fitted with electronic weighing and data management terminal, suitable for applications such as formulation, piece counting, totalisation, memorisation of stock movements, bar code reading, printouts, labelling, etc. The wide range of available interfaces and software applications make this instrument truly be a mobile weighing station integrated to a company's computer system.

Available also CE-M APPROVED

Maximum lifting capacity: 2000kg.
Accuracy: +/- 0.1% of the maximum capacity.
Fork dimensions 1150x550x85mm. Weighs about 125kg.
Bearing structure in extra thick sheet steel and oven-fire painted interior construction.

Fitted swivelling column head .

Steering wheels and double loading rollers with a polyurethane coating.
4 shear-beam load cells.

Weighing indicator with easy to clean **ABS waterproof IP65** enclosure built to withstand humid and dusty environments
highly efficient red LED 6 digit 15mm display large alphanumeric backlit LCD display with 2 lines of 16 char. 9 mm high, which are clearly visible evening poor lighting conditions. 24-key alphanumeric and functional waterproof keyboard. Indication of active functions through 16 bright indication LEDs. Configuration, calibration and diagnostics from keyboard.

Power supply through built-in rechargeable battery. The operating time is of about 40 hours of continuous use or three months with the typical non continuous use, thanks to its auto switch-off function.

Programmable auto power saving function.
Battery level indication. Equipped with 230 Vac 50 Hz battery charger (recharging time is about 8 hours).

Formulation functioning as PC terminal (data entry protocol communication) database of 1000 articles 200 customers/suppliers, 300 tares, 4 independent viewable and printable total levels, bar code reading with article activation 15 configurable and printable text IDs (i.e.: Code, lot ID, operator ID, shift number, etc.), A.C.W. (Automatic Calibration Warning): automatically advises to check the configurable calibration. Customisable printouts.

transmission/WI -FI.

Alibi memory.

Control light.

Parking brake. Special versions by price estimate: 680 mm fork width special fork length from 850 to 1500 mm 3000 kg capacity, high resolution. Special wheels available with price estimate.

Configurable full-duplex RS232/C port for connection to printer or labeller.

Configurable full-duplex RS232/C port for PC with RJ connector for fast connection.

Three 0.5A 48Vac/1A 24Vdc relay outputs (NO or NC). 2 optoisolated inputs configurable as remote function keys. Time/date.

IR input for managing remote control.

TPW20E02 Advanced Counting function of quantities

(pieces, liters, etc.) in loading, in extraction, counting of remnants functioning as PC terminal (data entry communication protocol) database of 1000 articles 200 customers/suppliers, 300 tares, 4 independent viewable and printable total levels, bar code reading with article activation, A.C.W. (Automatic Calibration Warning): automatically advises to check the configurable calibration. Customisable printouts.



TPW20E01 Advanced totalisation, in loading/unloading, totalisation Formulation +/- Check Weigh percentile Counting In/Out weighing Hold Set Point control Database management of 200 articles and 100 tares. Complete customisation of the

Extractable rechargeable battery power supply.

Thermal printer

Virtual printer integrated with Memory Card. Thermal

and Virtual printer integrated with Memory Card. Radio

Code	Max Capacity kg	Division kg	CE-M Division kg	Price €
TPW20E	500 / 1000 / 2000	0,2 / 0,5 / 1		2.150.00
TPW20EM 	1000 / 2000		0,5 / 1	2.580.00
TPW20E01	500 / 1000 / 2000	0,2 / 0,5 / 1		2.530.00
TPW20E01M 	1000 / 2000		0,5 / 1	2.930.00
TPW20E02	500 / 1000 / 2000	0,2 / 0,5 / 1		2.530.00
TPW20E02M 	1000 / 2000		0,5 / 1	2.930.00

Code	Description	Price €
TPWXFI	Pair of stainless steel forks.	1.170,00
TPWRAS	Antistatic driving wheels.	160,00
TPRPL	Thermal printer for mounting on the pallet truck column. (For mounting with extractable battery order only the TPWLBKPT option)	400,00
TPWLMMC	Virtual printer for mounting on the pallet truck column, complete of memory card. (not available with the mounting of the extractable battery)	340,00
TPWLMDP	Thermal printer and memory data for mounting on the pallet truck column, complete of memory card. (not available with the mounting of the extractable battery)	620,00
RFITR	Integrated 868 MHz radio frequency module on the indicator, complete of RS232 port. Max. functioning distance in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. Up to 50 configurable channels. (RFITR must be combined with another radio module).	350,00
OBRFUSB	868 MHz radio frequency module for PC, with PVC box and 1 m USB/mini USB connecting cable; power supply directly from the USB port. Max. functioning distance, in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. 50 configurable channels. (OBRFUSB must be combined with another radio module).	480,00
OBRF232	868 MHz radio frequency module for PC, with PVC box, 3 m RS232 connecting cable complete with DB9 pin connector and power supply. Max. functioning distance, in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. 50 configurable channels. (OBRF232 must be combined with another radio module).	480,00
35ALMEM	Alibi memory (fiscal memory, max 120.000 weighs) for approved transmission of the weight.	130,00
DFTL	Remote control for use up to 8 m of distance.	80,00
WIFIT	WI-FI interface for wireless connection (through access point) to the company computer system.	500,00
TPWFRE	Parking brake system with command pedal mounted on steering wheels.	210,00
TPWLBK	Extractable battery mounted on the pallet truck column to be used with the charger fitted with the scale.	120,00
TPWBKB	Additional extractable battery for using the scale 24/7. (To be combined to TPWLBK option)	120,00
TPWLBKPT	Thermal printer and extractable battery mounted on the pallet truck column to be used with the charger fitted with the scale.	500,00
IFKBRD	Keyboard input and third serial for connection to PC keyboard / bar code reader (to be combined with KBCBC cable with mini DIN connector) and for remote scale / weight repeater management.	210,00
KBCBC	Cable with MINI DIN connector for PC keyboard or badge/barcode reader connection (must be combined with IFKBRD serial interface).	80,00

Code	Description	Price €
SCCD	Bar code scanner connectable to the indicator through the keyboard input (fitted on the "Enterprise" indicators or with IFKBRD option on the other model) and cable with mini DIN connector (optional). Reads the main barcodes such as UPC/EAN, Code 39, Code 39 Full ASCII, Interleave 25, Code 128 and others; reading width of 60 mm; max. reading distance: 20 mm / 20 mil.	150,00
UKPLUG	Power adapter from Schuko to BS1363.	20,00